



Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2 μ m/80 μ m Ni, 5 μ m/200 μ Sn

Gold Plated:2 μ m/80 μ m Ni, 0.8 μ gold

Insulator:PPS UL94V-0

Electrical:

Current rating:1Amps/contact max.

Contact resistance: $\leq 4m\Omega$ /contact

Insulation resistance: $\geq 1000M\Omega$ at V=100V

Dielectric Withstanding Voltage:1000V AV Min

Operating voltage:60VAC/DC

Mechanical:

Operating temperature:-40° C to+105° C

Soldering temperature:+255° C

Serial number	No. of Positions	PART NO	A	B
1	24	STOB4-I124XX1000A	21.80	19.558
2	28	STOB4-I128XX1000A	25.20	23.114
3	30	STOB4-I130XX1000A	27.00	24.892
4	32	STOB4-I132XX1000A	28.80	26.67
6	48	STOB4-I148XX1000A	43.10	40.894

TOLERANCE:

X. $\pm XXX$

.X ± 0.20

.XX ± 0.10

ANG.



上海狮拓电子科技有限公司

產品名稱:

產品料號:

THIRD ANGLE PROJECTION



簽名 _____

日期 _____

審核 _____

日期 _____

客戶確認

承認 _____ 日期 _____

駁回 _____ 日期 _____