



Technical Data

Material:

Pin(outer sleeve):Brass,machined CuZn38Pb2

Plating(outer sleeve):

Tin Plated:2 μ m/80 μ m²Ni, 5 μ m/200 μ ²Sn

Gold Plated:2 μ m²/80 μ m²Ni, 0.8 μ ² gold

Insuiator:PPS UL94V-0

Electrical:

Current rating:1Amps/contact max.

Contact resistance: $\leq 4m\Omega$ /contact

Insuiation resistance: $\geq 1000M\Omega$ at V=100V

Dlelectric Withstanding Voltage:1000V AV Min

Operaling voitage:60VAC/DC

Mechanical:

Operaling temperature:-40 $^{\circ}$ C to+105 $^{\circ}$ C

Soldering temperature:+255 $^{\circ}$ C

Serial number	No. of Positions	PART NO	A	B
7	20	STOB5-I120XX1000A	18.1	16.002
8	24	STOB5-I124XX1000A	21.7	19.558
9	28	STOB5-I128XX1000A	25.2	23.114
10	40	STOB5-I140XX1000A	35.8	33.782
11	42	STOB5-I142XX1000A	37.7	35.56
12	48	STOB5-I148XX1000A	43.1	40.894
13	52	STOB5-I152XX1000A	46.7	44.45
14	56	STOB5-I156XX1000A	50.2	48.006
15	64	STOB5-I164XX1000A	57.3	55.118
14	68	STOB5-I168XX1000A	60.9	48.674

TOLERANCE:

.X. $\pm XXX$

.X ± 0.20

.XX ± 0.10

ANG.



上海狮拓电子科技有限公司

產品名稱:

產品料號:

THIRD ANGLE PROJECTION

簽名 _____

日期 _____

審核 _____

日期 _____

客戶確認

承認 _____ 日期 _____

駁回 _____ 日期 _____